

Header-Transporter

Easy loading, safe transportation.

FOR

**CASE IH
NEW HOLLAND**



The complete family of header transporters

For safe travel on all roads.

A good transporter is essential to achieve a fast field-to-field changeover without damage to combine or header. Our header transporters are made for fast and easy loading.

With the robust header transporters from Zürn you transport your cutting platforms quickly and safely to your destination.

Header size	1-Axle Header Transporter	2-Axle Header Transporter	2-Axle Header Transporter with All-Wheel-Steering
5.50 m (18 ft)	•		
6.10 m (20 ft)	•		
6.70 m (22 ft)	•		
7.60 m (25 ft)	•	•	
9.15 m (30 ft)		•	•
10.70 m (35 ft)		•	•
12.50 m (41 ft)			•



Customized and tailored header transporters

The Zürn product range offers appropriate transport solutions for every cutting width. Our header transporters are customised and tailored to the particular combine and header model. For safe travel on the road, all our header transporters are homologated according to the strictest regulations (e.g. in Germany and France).



Header supports for easy loading

The large over dimensioned supports with V-Lock mechanism are made for easy loading and to protect the header even on tough road conditions.



SWW 100 - SWW 200 - SWW 300

1-Axle Header Transporter

- ▶ Recommended for headers from 16 ft (4.90 m) to 25 ft (7.60 m)
- ▶ Unbraked; parking brake and overrun brake with auto-reverse as option



SWW 500

2-Axle Header Transporter

- ▶ Recommended for headers from 22 ft (6.70 m) to 30 ft (9.15 m)
- ▶ Large track width and wide pendulum front axle with turntable steering for very large steering angles and maximum stability
- ▶ Parking brake and overrun brake with auto-reverse as standard



SWW X2

2-Axle Header Transporter with 4-wheel-steering (2-axle turntable steering)

- ▶ Recommended for headers from 25 ft (7.60 m) to 35 ft (10.70 m)
- ▶ Reliable, mechanical 2-axle turntable steering with large steering angle (45°) is easy to adjust
- ▶ Header transporter follows the combine in consistent alignment
- ▶ Low loading height for all combines
- ▶ Parking brake and overrun brake with auto-reverse as standard



SWW X6

2-Axle Header Transporter with 4-wheel-steering (4-wheel axle-pivot steering)

- ▶ Recommended for headers from 30 ft (9.15 m) to 45 ft (13.70 m)
- ▶ Reliable, mechanical 2-axle turntable steering with very large steering angle (70°) is easy to adjust
- ▶ Header transporter follows the combine in consistent alignment
- ▶ Compatible with all header types and combines due to extra low loading height



Zürn Harvesting GmbH & Co KG

Kapellenstr. 1 · 74214 Schöntal-Westernhausen · Germany
Tel.: +49 7943 9105-0 · Fax: +49 7943 9105-33

info@zuern.de · www.zuern.de

This literature has been compiled for worldwide circulation. Some illustrations and text may include product options and accessories not available in all regions. Please contact your local dealer for details. Zürn Harvesting reserves the right to change specification and design to products described in this literature without notice.

UK | SWW FLYER CNH | 09/2019

ZÜRN
H A R V E S T I N G

